

Page: 1/11

Revised edition n°: 10.0

Revision date: 10/2023

MTGXXX

R407A

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name R407A

Chemical description Refrigerant mixture HFC (Difluoromethane, Pentafluoroethane, 1,1,1,2-

Tetrafluoroethane)

CAS N° -

CE N° Index N° -

Registration n° -

Chemical formula CH₂F₂, C₂HF₅, CH₂FCF₃

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Industrial and professional

Test gas/Calibration gas

Use for manufacture of electronic/photovoltaic components

Use as refrigerant Laboratory use

Contact supplier for more information on uses

Uses advised against For use by industrial or professional users only

1.3. Details of the supplier of the safety data sheet

MULTIGAS

Company identification Route de l'Industrie 102

CH-1564 Domdidier

Phone number +41 (0) 26 676 94 94

E-mail address <u>info@multigas.ch</u>

1.4. Emergency telephone numbers

145 (Toxicology Centre Zurich) or +41 (0) 44 251 51 51

+41 (0) 26 676 94 94 (Multigas)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Gases under pressure : Liquefied gas

H280



Page : 2/11

Revised edition n°: 10.0 Revision date: 10/2023

MTGXXX

R407A

For the complete H-sentences texts mentioned in that chapter, refer to Section 16

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms

 \Diamond

GHS04

Signal word Warning

Hazard statements

H280 Contains gas under pressure; may explode if heated

Precautionary statements

P410+403 Protect from sunlight. Store in a well-ventilated place

2.3. Other hazards

None

SECTION 3: Composition/information on ingredients

3.1. Substances

Name	Product identifier	Concentration	Classification
Pentafluoroethane (R 125)	(CAS-No.) 354-33-6 (EC-No.) 206-557-8 (EC Index-No.) (Registration-No.) 01-2119485636-25	40 %	Press. Gas (Liq.), H280
1,1,1,2-Tetrafluoroethane (R 134A)	(CAS-No.) 811-97-2 (EC-No.) 212-377-0 (EC Index-No.) (Registration-No.) 01-2119459374-33	40 %	Press. Gas (Liq.), H280
Difluoromethane (R32)	(CAS-No.) 75-10-5 (EC-No.) 200-839-4 (EC Index-No.) (Registration-No.) 01-2119471312-47	20 %	Flam. Gas 1 H220 Press. Gas (Liq.) H280

For the complete H-sentences texts mentioned in that chapter, refer to Section 16 Contains no other components or impurities which will influence the classification of the product



Page: 3/11

Revised edition n°: 10.0 Revision date: 10/2023

MTGXXX

R407A

3.2. Mixtures

Not established

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice See a doctor. Show this safety data sheet to the attending physician

In case of inhalation In case of inhalation, remove the person from the contaminated area. In

case of respiratory arrest, give artificial respiration. See a doctor

In case of skin contact

No adverse effects expected

In case of eyes contact Immediate washing, abundant and prolonged with water. If irritation

persists, consult a doctor

In case of ingestion Do NOT induce vomiting. Never give anything by mouth to an unconscious

person. Rinse mouth with water. See a doctor

4.2. Most important symptoms and effects, both acute and delayed

Refer to section 11

4.3. Indication of any immediate medical attention and special treatment needed

Do not give adrenaline or similar drugs

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Water spray or water mist. Dry powder. Carbon dioxide. Foam

Unsuitable extinguishing mediaDo not use water jet to extinguish

5.2. Special hazards arising from the substance or mixture

Specific hazards In case of fire or excessive heat, hazardous combustion products may be

produced

Exposure to fire may cause containers to rupture/explode

Hazardous combustion products In case of fire or excessive heat, hazardous combustion products may be

produced such as: carbonyl fluoride, carbon monoxide, hydrogen fluoride

5.3. Additional information

Cool endangered receptacles with water spray jet from a protected position



Page : 4/11

Revised edition n°: 10.0 Revision date: 10/2023

MTGXXX

R407A

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid breathing vapours, spray mists or gases

Provide adequate ventilation

Evacuate personnel to a safe place

Personal protective equipment, see section 8

6.2. Environmental precautions

-

6.3. Methods and material for containment and cleaning up

Ventilate the area

6.4. Reference to other sections

See also sections 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For precautions, see section 2.2

7.2. Conditions for safe storage, including any incompatibilities

Store in a cool place. Keep container tightly closed in a dry and well-

ventilated place

Content under pressure

7.3. Specific end use(s)

None

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Components with occupational exposure limits

Component	CAS N°	Exposure value type	Control parameter	Source
Pentafluoroethane (R125)	354-33-6	TWA	-	No occupational exposure limit value
			-	
		OEL	-	
			-	



Page : 5/11

Revised edition n°: 10.0 Revision date: 10/2023

MTGXXX

R407A

1,1,1,2-Tetrafluoroethane (R134A)	811-97-2	TWA	1000 ppm	SUVA: Limit values of exposure to workstations
			4 240 mg/m ³	
		OEL	-	SUVA: Limit values
			-	of exposure to workstations
Difluoromethane (R32)		TWA	-	No occupational exposure limit value
	75 40 F		-	
	75-10-5	OEL	-	
			-	

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Provide adequate general and local exhaust ventilation

Gas detectors should be used when flammable / toxic gases / vapours are

likely to be released

8.2.2. Individual protection measures, e.g. personal protective equipment

Eye/face protection Wear goggles and a face shield when transfilling or breaking transfer

connections. Standard EN 166

Skin / hand protection Wear protective gloves when handling gas cylinders

The selected protective gloves have to satisfy the specifications of EU

Directive 89/686 / EEC and the standard EN 374 derived from it

For long-term use

Material: Fluoroelastomer Penetration time: 480 min Glove thickness: 0.7 mm For short-term use Material: Fluoroelastomer Penetration time: 480 min Glove thickness: 0.7 mm

Have appropriate, chemical-resistant protective clothing ready for use in

emergencies

Respiratory protection Self-contained breathing apparatus (SCBA) or positive pressure air mask

must be used in oxygenated atmospheres. Standard EN 137 - Self-

contained compressed air device with a full face mask

8.2.3. Environmental exposure controls

_



Page: 6/11

Revised edition n°: 10.0 Revision date: 10/2023

MTGXXX

R407A

Gas

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state at 20°C /

101.3kPa

• Colour Colourless

Odour Slightly ethereal

Odour threshold No data available

pH No data available

Melting point / Freezing point No data available

Boiling point -45.5°C to -38.9°C

Flash point No data available

Evaporation rate No data available

Flammability (solid, gas) Non-flammable

Explosive limits No data available

Vapour pressure [20°C] 11 bar

Vapour pressure [50°C] 23.2 bar

Vapour density 2.54

Relative density, liquid (water=1) 1.17

Relative density, gas (air=1) 3

Water solubility Poorly soluble in water

Partition coefficient No data available

n-octanol/water (Log Kow)

Auto-ignition temperatureNo data availableDecomposition temperatureNo data availableViscosityNo data availableExplosive propertiesNo data availableOxidising propertiesNo data available

9.2. Other information

Molar mass90.1 g/molCritical temperature [°C]82°CCritical pressure45 bar

Relative vapour density

Gas/vapour heavier than air. May accumulate in confined spaces,

particularly at or below ground level



Page: 7/11

Revised edition n°: 10.0 Revision date: 10/2023

MTGXXX

R407A

SECTION 10: Stability and reactivity

10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below

10.2. Chemical stability

Stable under recommended storage conditions

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Alkaline and alkaline earth metals, strong oxidizers, finely divided metals For additional information on compatibility refer to ISO 11114

10.6. Hazardous decomposition products

At high temperatures, thermal decomposition into highly toxic and corrosive products, including :

- Hydrogen fluoride
- Carbon oxides

SECTION 11: Toxicological information

11.1. Chemical safety assessment

Acute toxicity Not harmful by inhalation

Skin corrosion/irritation

Serious eye damage/irritation

Respiratory or skin sensitisation

Germ cell mutagenicity

Carcinogenicity

Reproductive toxicity

STOT-single exposure – Target

No data available

No data available

No data available

organ(s)

organ(3)

No doto ovojloblo

STOT-repeated exposure No data available
Ingestion hazard No data available

11.2. Information on other hazards

The substance/mixture has no endocrine disrupting properties



Page: 8/11

Revised edition n°: 10.0 Revision date: 10/2023

MTGXXX

R407A

SECTION 12: Ecological information

12.1. Toxicity

Assessment Not very harmful for fish

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

PBT / vPvB assessment is not available because the chemical safety

assessment is not required / is not conducted

12.6. Endocrine-disrupting properties

No data available

12.7. Other adverse effects

Contains fluorinated greenhouse gas(es)

Global warming potential (GWP) (CO2 = 1): 2107 Ozone Depletion Potential (ODP) (R-11 = 1): 0

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product Must not be released into the atmosphere

Burn in a chemical incinerator equipped with an afterburner and scrubber Return to the supplier the product not consumed in its original container

Contaminated container

Return to the supplier the product not consumed in its original container

OMoD Code 14 06 01

Solvent, refrigerant and aerosol propellant or organic foam wastes:

Chlorofluorocarbons, HCFCs, HFCs



Page : 9/11

Revised edition n°: 10.0

Revision date: 10/2023

MTGXXX

R407A

SECTION 14: Transport information

14.1. UN number

Transport par road/rail ADR / RID	Transport by sea IMDG	Transport by air IATA
3338	3338	3338

14.2. UN proper shipping name

Transport par road/rail ADR / RID	Transport by sea IMDG	Transport by air IATA
Refrigerant gas R 407A	Refrigerant gas R 407A	Refrigerant gas R 407A

14.3. Transport hazard class(es)

Labelling

2

ADR/RID IMDG IATA

2.2 : Non-flammable, non-toxic gases

14.4. Packing group

ADR/RID IMDG IATA

Not established

14.5. Environmental hazards

ADR/RID None
IMDG None
ICAO-TI / IATA-DGR None

14.6. Special precautions for user

No data available

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture



Page : 10/11

Revised edition n°: 10.0 Revision date: 10/2023

MTGXXX

R407A

This safety data sheet complies with the requirements of Regulation (CE) No. 1907/2006

15.2. Chemical safety assessment

A CSA has not been made yet

SECTION 16: Other information

Indication of changes Revised safety data sheet in accordance with commission regulation (EU)

No 2015/830

Abbreviations and acronyms ADR: European Agreement concerning the International Carriage

of Dangerous Goods by Road

CAS: Chemical Abstract Service number (USA)

CLP: Classification Labelling Packaging Regulation; Regulation

(EC) No 1272/2008

CSA: Chemical Safety Assessment

EIGA: European Industrial Gases Association

EINECS: European Inventory of Existing Commercial Chemical

Substances

EN: European Standard
ATE: Acute Toxicity Estimate

IATA: International Air Transport Association

IMDG Code: International Maritime Dangerous Goods Code
LC50: Lethal Concentration to 50 % of a test population
OMoD: Swiss Ordinance on the movement of waste

PBT : Persistent, Bioaccumulative and Toxic

PPE: Personal Protection Equipment

REACH: Registration, Evaluation, Authorisation and Restriction of

Chemicals Regulation (EC) No 1907/2006

RID: Regulations concerning the international carriage of

dangerous goods by rail

RMM: Risk Management Measures

STOT-SE: Specific Target Organ Toxicity - Single Exposure

UN: United Nations

vPvB: Very Persistent and Very Bioaccumulative

WGK: Water Hazards Class

Full text of H, EUH and P statements used in sections 2 and 3

Hazard statements

H280 Contains gas under pressure; may explode if heated

Precautionary statements

P410+403 Protect from sunlight. Store in a well-ventilated place



Page : 11/11

Revised edition n°: 10.0 Revision date: 10/2023

MTGXXX

R407A

Disclaimer of liability

Details given in this document have been prepared based on the most available reliable documents and are believed to be correct at the time of going to press

They do not claim to be exhaustive and should be considered as a guide