	SAFETY DATASHEET	Page : 1/12
		Revised edition n° : 10.2
		Revision date : 01/2023
Ethylene oxide		MTG056

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name	Ethylene oxide
Chemical description	Ethylene oxide
CAS N°	75-21-8
CE N°	200-849-9
Index N°	603-023-00-X
Registration n°	01-2119432402-53
Chemical formula	C ₂ H ₄ O

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Industrial and professional Test gas/Calibration gas Laboratory use Chemical reaction / Synthesis Contact supplier for more information on use
Uses advised against	Consumer use not recommended

1.3. Details of the supplier of the safety data sheet

Company identification	MULTIGAS Route de l'Industrie 102 CH-1564 Domdidier
Phone number	+41 (0) 26 676 94 94
E-mail address	info@multigas.ch

1.4. Emergency telephone numbers


145 (Toxicology Centre Zurich) or +41 (0) 44 251 51 51
 +41 (0) 26 676 94 94 (Multigas)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable gases, Category 1	H220
Chemically unstable gases, Category A	H230

	SAFETY DATASHEET	Page : 2/12
		Revised edition n° : 10.2
		Revision date : 01/2023
Ethylene oxide		MTG056

Gases under pressure : Liquefied gas	H280
Acute toxicity, (ingestion) Category 3	H301
Skin corrosion/irritation, Category 1	H314
Serious eye damage/eye irritation, Category 1	H318
Acute toxicity (inhalation: gas) Category 3	H331
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation	H335
Toxicité spécifique pour certains organes cibles — Exposition répétée, Catégorie 3	H336
Germ cell mutagenicity, Category 1B	H340
Carcinogenicity, Category 1B	H350i
May impair fertility. May cause harm to the foetus. Category 1B	H360Fd
Specific target organ toxicity — Repeated exposure, Category 1	H372

For the complete H-sentences texts mentioned in that chapter, refer to Section 16

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms




GHS02 GHS04 GHS05 GHS06 GHS8

Signal word

Danger

Hazard statements

H220	Extremely flammable gas
H230	May react explosively even in the absence of air
H280	Contains gas under pressure; may explode if heated
H301	Toxic if swallowed
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H331	Toxic if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350i	May cause cancer
H360Fd	May damage fertility or the unborn child
H372	Causes damage to organs through prolonged or repeated exposure

	SAFETY DATASHEET	Page : 3/12
		Revised edition n° : 10.2
		Revision date : 01/2023
Ethylene oxide		MTG056

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P260	Do not breathe gas, vapours
P280	Wear protective gloves, protective clothing, eye protection, face protection
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
P303+P361+P353+P315	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Get immediate medical advice/attention
P304+P340+P315	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get immediate medical advice / attention
P305+P351+P338+P315	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice / attention
P410+P403	Protect from sunlight. Store in a well-ventilated place
P405	Store locked up

2.3. Other hazards

None


SECTION 3: Composition/information on ingredients

3.1. Substances

Name	Product identifier	Concentration	Classification
Ethylene oxide	(CAS-No.) 75-21-8 (EC-No.) 200-849-9 (EC Index-No.) 603-023-00-X (Registration-No.) 01-2119432402-53	≥ 99.9%	Flam. Gas 1, H220 Chem. Unst. Gas A, H230 Press. Gas (Liq.), H280 Acute Tox 3, H301 Acute Tox. 3 (Inhalation: gas), H331 Skin Irrit. 1, H314 Eye Irrit. 1, H318 Muta. 1B, H340 Carc. 1B, H350i Repr. 1B, H360Fd STOT SE 3, H335 STOT SE 3, H336 STOT RE 1, H372

For the complete H-sentences texts mentioned in that chapter, refer to Section 16

Contains no other components or impurities which will influence the classification of the product

	SAFETY DATASHEET	Page : 4/12
		Revised edition n° : 10.2
		Revision date : 01/2023
Ethylene oxide		MTG056

3.2. Mixtures

Not established

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	See a doctor. Show this safety data sheet to the attending physician
In case of inhalation	In case of inhalation, remove the person from the contaminated area. In case of respiratory arrest, give artificial respiration. See a doctor
In case of skin contact	Wash with soap and plenty of water. See a doctor
In case of eyes contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a doctor
In case of ingestion	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. See a doctor

4.2. Most important symptoms and effects, both acute and delayed

May cause irritation to cornea (with temporary disturbance to vision)
 May cause irritation to skin
 May cause irritation to the respiratory tract, sneezing, coughing, burning sensation of throat with constricting sensation of the larynx and difficulty in breathing
 Refer to section 11

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media


Suitable extinguishing media	Extinguishing powder. Alcohol-resistant foam. Water spray
Unsuitable extinguishing media	Do not use a water jet. Carbon dioxide

5.2. Special hazards arising from the substance or mixture

Specific hazards	In case of fire or excessive heat, hazardous combustion products may be produced Exposure to fire may cause containers to rupture/explode
Hazardous combustion products	In case of fire or excessive heat, hazardous combustion products may be produced such as : carbon monoxide

5.3. Additional information

Exposure to fire may cause containers to rupture/explode

	SAFETY DATASHEET	Page : 5/12
		Revised edition n° : 10.2
		Revision date : 01/2023
Ethylene oxide		MTG056

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid breathing vapours, spray mists or gases
 Provide adequate ventilation
 Remove all sources of ignition
 Evacuate the staff to safe place
 Beware of vapours that accumulate forming explosive concentrations
 Vapours may accumulate in low areas
 Personal protective equipment, see section 8

6.2. Environmental precautions

Try to stop the leak

6.3. Methods and material for containment and cleaning up

Ventilate the area
 Keep area evacuated and free from ignition sources until any spilled liquid has evaporated (ground free from frost)

6.4. Reference to other sections

See also sections 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling


Avoid contact with skin and eyes. Avoid breathing vapour or mist
 Keep away from sources of ignition - No smoking Take measures to prevent the accumulation of electrostatic charges
 For precautions, see section 2.2

7.2. Conditions for safe storage, including any incompatibilities

Store in a cool place. Keep container tightly closed in a dry and well-ventilated place
 Do not expose to temperatures above 50°C

7.3. Specific end use(s)

None

	SAFETY DATASHEET	Page : 6/12
		Revised edition n° : 10.2
		Revision date : 01/2023
Ethylene oxide		MTG056

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Components with occupational exposure limits

Component	CAS N°	Exposure value type	Control parameter	Source
Ethylene oxide	75-21.8	TWA	1 ppm	SUVA: Limit values of exposure to workstations
			1.8 mg/m ³	
		OEL	-	SUVA: Limit values of exposure to workstations
			-	

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Product to be handled in a closed system
 Provide adequate general and local exhaust ventilation
 Gas detectors should be used when toxic gases may be released

8.2.2. Individual protection measures, e.g. personal protective equipment

Eye/face protection

Wear goggles and a face shield when transfilling or breaking transfer connections
 Standard EN 166 - Personal eye-protection - specifications

Skin / hand protection

Wear protective gloves when handling gas cylinders. Standard EN 388
 Wear cold insulating gloves when transferring or disconnecting transfer lines Standard EN 511
 Wearing chemical resistant gloves Standard EN 374

For short-term use
 Material: Butyl rubber
 Penetration time: >30 min
 Glove thickness: 0.7 mm

For long-term use
 Material: Butyl rubber
 Penetration time: >480 min
 Glove thickness: 0.7 mm

Have appropriate, chemical-resistant protective clothing ready for use in emergencies. Standard EN943-1

Respiratory protection

Self-contained breathing apparatus (SCBA) or positive pressure air mask must be used in oxygenated atmospheres. Standard EN 137 - Self-contained compressed air device with a full face mask

8.2.3. Environmental exposure controls


-

Ethylene oxide
MTG056
SECTION 9: Physical and chemical properties
9.1. Information on basic physical and chemical properties
Appearance

• Physical state at 20°C / 101.3kPa	Gas
• Colour	Colourless
Odour	Ethereal
Odour threshold	No data available
pH	No data available
Melting point / Freezing point	-112°C
Boiling point	10.4°C
Flash point	-57°C (closed cup)
Evaporation rate	No data available
Flammability (solid, gas)	Extremely flammable gas
Explosive limits	2.6 – 100%
Vapour pressure [20°C]	1.45 bar
Vapour pressure [50°C]	3.95 bar
Vapour density	No data available
Relative density, liquid (water=1)	0.87
Relative density, gas (air=1)	1.56
Water solubility	Fully soluble
Partition coefficient n-octanol/water (Log Kow)	0.3
Auto-ignition temperature	435°C
Decomposition temperature	~570°C
Viscosity	No data available
Explosive properties	No data available
Oxidising properties	No data available

9.2. Other information

Molar mass	44.05 g/mol
Critical temperature [°C]	195.8°C
Relative vapour density	1.56
	Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level

	SAFETY DATASHEET	Page : 8/12
		Revised edition n° : 10.2
		Revision date : 01/2023
Ethylene oxide		MTG056

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

Stable under recommended storage conditions

10.3. Possibility of hazardous reactions

Risk of polymerisation
 Reacts with many chemical compounds
 Reacts with light metals
 Reacts with alkali metals
 Reactions with amines

10.4. Conditions to avoid

Light
 Heat sources / heat - risk of bursting
 Water / moisture
 Sources of ignition, open flames, glowing metal surfaces, etc.

10.5. Incompatible materials

Alcohols, alkali metals, ammonia, oxidants, chemically active metals and their salts
 For more information on compatibility, refer to ISO 11114


10.6. Hazardous decomposition products

Hazardous decomposition products formed under fire conditions: carbon oxide

SECTION 11: Toxicological information

11.1. Chemical safety assessment

Acute toxicity	Toxic if inhaled and ingestion
Skin corrosion/irritation	Causes serious skin irritation
Serious eye damage/irritation	Causes serious eye irritation
Respiratory or skin sensitisation	No data available
Germ cell mutagenicity	May cause genetic defects
Carcinogenicity	May cause cancer
Reproductive toxicity	May impair fertility. May cause harm to the foetus
STOT-single exposure – Target organ(s)	May cause respiratory irritation May cause drowsiness and dizziness

	SAFETY DATASHEET	Page : 9/12
		Revised edition n° : 10.2
		Revision date : 01/2023
Ethylene oxide		MTG056

STOT-repeated exposure	Damage to red blood cells (haemolytic poison) Affects the nervous system and haematopoietic organs in case of prolonged or repeated exposure by inhalation
Ingestion hazard	No data available

SECTION 12: Ecological information

12.1. Toxicity

Assessment	Toxic by inhalation
-------------------	---------------------

12.2. Persistence and degradability

The substance is readily biodegradable. Unlikely to persist

12.3. Bioaccumulative potential

Not expected to bioaccumulate due to the low log Kow (log Kow < 4)
Refer to section 9

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

PBT / vPvB assessment is not available because the chemical safety assessment is not required / is not conducted


12.6. Other adverse effects

May cause pH changes in aqueous ecological systems

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product	Must not be discharged to atmosphere Burn in a chemical incinerator equipped with an afterburner and scrubber Return surplus and non-recyclable solutions to a licensed waste disposal company
Contaminated container	Return surplus and non-recyclable solutions to a licensed waste disposal company Contact the supplier if instructions are needed
OMoD Code	16 05 04 Gases in pressure containers (including halons) containing dangerous substances

	SAFETY DATASHEET	Page : 10/12
		Revised edition n° : 10.2
		Revision date : 01/2023
Ethylene oxide		MTG056

SECTION 14: Transport information

14.1. UN number

Transport par road/rail ADR / RID	Transport by sea IMDG	Transport by air IATA
1040	1040	1040

14.2. UN proper shipping name

Transport par road/rail ADR / RID	Transport by sea IMDG	Transport by air IATA
Ethylene oxide with nitrogen	Ethylene oxide with nitrogen	Ethylene oxide

14.3. Transport hazard class(es)

Labelling



ADR/RID
IMDG
IATA

2.3 : Toxic gases
2.1 : Flammable gases

14.4. Packing group

ADR/RID
IMDG
IATA

Not established

14.5. Environmental hazards

ADR/RID

None

IMDG

None

ICAO-TI / IATA-DGR

None

14.6. Special precautions for user


No data available

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

	SAFETY DATASHEET	Page : 11/12
		Revised edition n° : 10.2
		Revision date : 01/2023
Ethylene oxide		MTG056

This safety data sheet complies with the requirements of Regulation (CE) No. 1907/2006

15.2. Chemical safety assessment

A CSA has been carried out

SECTION 16: Other information

Indication of changes

Revised safety data sheet in accordance with commission regulation (EU) No 2015/830

Abbreviations and acronyms

ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road

CAS : Chemical Abstract Service number (USA)

CLP : Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008

CSA : Chemical Safety Assessment

DNEL: Derived no effect level

EIGA : European Industrial Gases Association

EINECS : European Inventory of Existing Commercial Chemical Substances

EN : European Standard

ATE : Acute Toxicity Estimate

IATA : International Air Transport Association

IMDG Code : International Maritime Dangerous Goods Code

LC50 : Lethal Concentration to 50 % of a test population

OMoD : Swiss Ordinance on the movement of waste

PBT : Persistent, Bioaccumulative and Toxic

PPE: Personal Protection Equipment

REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006

RID : Regulations concerning the international carriage of dangerous goods by rail

RMM : Risk Management Measures

STOT-SE : Specific Target Organ Toxicity - Single Exposure

UN : United Nations

vPvB : Very Persistent and Very Bioaccumulative

WGK: Water Hazards Class

Full text of H, EUH and P statements used in sections 2 and 3

Hazard statements

H220	Extremely flammable gas
H230	May react explosively even in the absence of air

Ethylene oxide

MTG056

H280	Contains gas under pressure; may explode if heated
H301	Toxic if swallowed
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H331	Toxic if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350i	May cause cancer
H360Fd	May damage fertility or the unborn child
H372	Causes damage to organs through prolonged or repeated exposure

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P260	Do not breathe gas, vapours
P280	Wear protective gloves, protective clothing, eye protection, face protection
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
P303+P361+P353+P315	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Get immediate medical advice/attention
P304+P340+P315	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get immediate medical advice / attention
P305+P351+P338+P315	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice / attention
P410+P403	Protect from sunlight. Store in a well-ventilated place
P405	Store locked up

Disclaimer of liability

Details given in this document have been prepared based on the most available reliable documents and are believed to be correct at the time of going to press

They do not claim to be exhaustive and should be considered as a guide